

Pump Features

- High strength plastic pump body with patented chamber design and cable structure
- Ergonomic handle design
- AISI 304 Shaft
- Max fluid temperature: +35oC
- Motor with thermal protector
- Protection Class: IPX8
- Max particle size 25mm

Technical Data

Pro Sub

- Power: 400W
- 1.25" Outlet
- Max Flow: 150 litres / minute
- Max Head: 5 metres
- Optimum Flow: 75 lpm @ 3m
- 10m power cable

Applications

- Submersible pump which can be used for both clean and dirty water
- Pump can remain fully submerged in water
- Domestic, industrial and agricultural use including emptying swimming pools

Pro Sub Plus

- Power: 750W
- 1.25" Outlet
- Max Flow: 150 litres / minute
- Max Head: 8 metres
- Optimum Flow: 125 lpm @ 5m
- 10m power cable

Pump Features

- Built-in thermal protector
- Aluminium Winding
- Insulation class F
- Protection Class IPX4
- Max ambient temperature +40oC
- Plastic pump body
- Max Fluid Temperature +35oC
- Max Suction +8m

Technical Data

STAWT50

- Power: 600W / 0.8 HP
- 1" Inlet / 1" Outlet
- Max Flow: 50 litres / minute
- Max Head: 35 metres
- Max Suction: 8 metres
- Optimum Flow: 30 lpm @ 20m
- Fitted with Stanley Pump Controller

Applications

- Transfer of clean water
- Water supply and draining in garden applications

STAWT75

- Power: 1100W / 1.5 HP
- 1" Inlet / 1" Outlet
- Max Flow: 77 litres / minute
- Max Head: 46 metres
- Max Suction: 8 metres
- Optimum Flow: 45 lpm @ 27m
- Fitted with Stanley Pump Controller

Pump Features

- Special anti-rust treatment for pump body and support
- AISI 304 Shaft
- Max fluid temperature: +40oC
- Max suction: +9m
- Copper winding
- Built in thermal protector for single phase motor
- Protection Class: IPX4
- Max ambient temperature: +40oC

Technical Data

STAPB40

- Power: 0.45kW / 0.6 HP
- 1" Inlet / 1" Outlet
- Max Flow: 40 litres / minute
- Max Head: 38 metres
- Max Suction: 9 metres
- Optimum Flow: 25 lpm @ 23m
- Fitted with Stanley Pump Controller

Applications

- Transfer of clean water
- Agricultural irrigation
- Industrial Use
- Pressure Boosting

STAPB60

- Power: 0.75kW / 1.0 HP
- 1" Inlet / 1" Outlet
- Max Flow: 60 litres / minute
- Max Head: 45 metres
- Max Suction: 9 metres
- Optimum Flow: 30 lpm @ 30m
- Fitted with Stanley Pump Controller

Pump Features

- AISI 304 pump body
- AISI 304 Shaft
- Max fluid temperature: +85oC
- Altitude up to 1000m
- Copper winding
- Protection Class: IPX4
- Max ambient temperature: +40oC

Technical Data

STAPB70

- Power: 0.55kW
- 1" Inlet / 1" Outlet
- Max Flow: 80 litres / minute
- Max Head: 29 metres
- Max Suction: 8 metres
- Rated Flow: 50 lpm @ 25m

Applications

- Transfer of clean water
- Water circulation
- Water treatment systems
- Agricultural irrigation

STAPB120

- Power: 0.55 kW
- 1.25" Inlet / 1" Outlet
- Max Flow: 160 litres / minute
- Max Head: 21 metres
- Max Suction: 8 metres
- Rated flow: 100 lpm @ 15m

Pump Features

- Copper winding
- Built in thermal protector
- Stainless steel welded shaft
- Insulation class B
- Protection class IP68
- Max immersion depth 5m
- Max liquid temperature +40oC
- 10m power cable

STAVTX75

- Power: 0.18kW / 0.25 HP
- Outlet 40,32,25 mm
- Max flow 133 lpm
- Max head 7m
- Optimum Flow: 87 lpm @ 4.5m
- Max particle diameter 15mm

Applications

- Wastewater in industrial and commercial facilities
- Drainage systems in sewage plants
- Drainage systems in residential applications
- Field irrigation in rural applications

STAVTX120

- Power: 0.45kW / 0.6 HP
- Outlet 50mm
- Max Flow: 200 litres / minute
- Max Head: 8.5 metres
- Optimum Flow: 120 lpm @ 6m
- Max particle diameter 25mm



Comprehensive range - Domestic and Industrial products - 2 Year Warranty - All models packaged in full colour cartons for strong retail presence - Reliable and well known brand

